

MECHANICAL PART

Publication number: EP0811789

Publication date: 1997-12-10

Inventor: SADA TAKASHI (JP)

Applicant: KOYO SEIKO CO (JP)

Classification:

- International: F01L1/16; F01L1/18; F16C13/00; F16C33/30;
F01L1/14; F01L1/18; F16C13/00; F16C33/30; (IPC1-7):
F16H53/06

- European: F01L1/16; F01L1/18; F16C13/00G; F16C33/30

Application number: EP19960938505 19961120

Priority number(s): WO1996JP03390 19961120; JP19950302763
19951121; JP19950302765 19951121

Also published as:

- WO9719278 (A1)
- US5997988 (A1)
- EP0811789 (A4)
- EP0811789 (B1)

Cited documents:


- DE4326768
- EP0661470
- US4834400
- US5456136
- JP8232964

[Report a data error here](#)

Abstract of EP0811789

A mechanical part having a rolling contact surface (11a) with many isolated minute recesses. A maximum height R_y of a roughness curve R obtained by cutting this contact surface (11a) with a plane perpendicular thereto is 1-3 μm , and a peak height R_p with respect to the center line of the roughness curve R and a valley depth R_v with respect thereto have the relation of $R_p/R_v \leq 0.3$. This indicates that the contact surface (11a) has very low peaks of a relatively high distribution and very deep valleys of a relatively low distribution. Owing to the very low peaks of a relatively high distribution, a sufficiently wide contact area is secured. Owing to the valleys of a low distribution and a large depth, oil reservoirs of a sufficient capacity are formed.

FIG. 1



Data supplied from the esp@cenet database - Worldwide